

HDI Waterborne DIC 5500

ABOUT:

The product data shown here are not sales specifications. When you import/use the product, you need to confirm whether the regulations of the country/region are applicable or not. Please refer to SDS concerning safety and handling of the product.

Description:

Water dispersible polyisocyanate hardener.

Applications:

Industrial coatings.

Protective coatings.

Wood coatings.

Hardener for 2K waterborne polyurethane coatings.

Key features:

Dispersibility in water.

Stability in water.

Compatible with main resins.

Characteristics:

Solvent	Methoxypropyl acetate
Solids content, %	79.0 - 81.0
Viscosity, Gardner	G - M
Acid value on solution, mgKOH/g	-
OH value on solution, mgKOH/g	13.0 - 14.0 (NCO content, %)
EEW, g/eq	-
pH	-
Color, Gardner	-

Storage and Transportation:

STORAGE: It is recommended to store in a dry and cool area with proper ventilation.

Packaging:

200KG/drum Please fasten the packaging cover as soon as possible after original packaging to prevent the mixing of other substances such as moisture and other substances that may affect the performance of the product. Do not inhale dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work, shower and change clothes.

Store contaminated clothes separately and reuse them after washing.

Maintain good hygiene practices.

E_mail us : info@allhdi.com