

HDI Waterborne WanHua 270

Product Description:

[Aquolin 270](#) is a water dispersible polyisocyanate based on hexamethylene diisocyanate (HDI). In combination with waterborne polyurethane, polyacrylate, etc., it can be used for water-borne coatings and adhesives. After addition of Aquolin 270, the ready-to-use mixture must be used within the pot life.

Aquolin 270 can be diluted with the solvents, such as propylene glycol methyl ether acetate (PMA), propylene glycol diacetate (PGDA), butyl acetate, etc. Only PU grade solvents (< 0.05% water) should be used and the solvents must be tested in advance by the user to determine suitability.

Properties:

1. High gloss and high building up.
2. Excellent weather resistance.
3. Excellent water dispersible and hand-mixing.

Characteristic data*

Property	Value	Unit	Method
Appearance	Colorless to yellow		

	wish transparent liquid		
NCO content	21.5±0.5	%	GB/T 12009.4-2016
Viscosity	1500-3500	mPa·s	Brookfield LV, 63#/3rpm, 25°C
Color APHA	<80		GB/T 1722-1992
Monomeric isocyanate	≤ 0.2	%	GB/T 18446-2009
Flash point	~196	°C	GB/T 5208
Density	~1.16	g/cm ³	GB/T 4472-2011

*These properties are typical but do not constitute specifications.

Storage:

The product should be stored in dry conditions above 5°C and below 35°C with the integrity of the packaging, and prevent direct sunlight. The validity of this product is for 12 months, performance assessment is recommended before use after shelf life. The product should be protected from freezing during storage. Water dispersible polyisocyanates are very moisture-sensitive and react with water to form carbon dioxide and insoluble ureas. The generation of carbon dioxide can lead to dangerous increases in pressure. The containers must always be kept tightly closed and the access of water

er in all forms must be prevented. It is suggested to use up once the package is open.

Packaging:

200KG/drum Please fasten the packaging cover as soon as possible after original packaging to prevent the mixing of other substances such as moisture and other substances that may affect the performance of the product. Do not inhale dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work, shower and change clothes. Store contaminated clothes separately and reuse them after washing. Maintain good hygiene practices.

E_mail us : info@allhdi.com